

## Polypropylene Fibre Rope 3-Strand.

---

### Product information



Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

**Design:** Spliced fibre.

**Specific gravity:** 0,91 (floats).

**Melting point:** Approx. 165°C.

**Elongation at MBL:** Approx. 30%.

**Strength wet/dry:** 100%

**Shock Absorption:** Very Good

**Water Absorption:** None

**Abrasion Resistance:** Good

... [Read more](#)

---

**Material:** Polypropylene, resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

**Marking:** According to standard

**Finish:** Blue.

**Standard:** EN ISO 1346

## Polypropylene Fibre Rope 3-Strand.

### Technical data

Part code	Diameter mm	MBL	Length m	Circ. inches	Weight kg/220m
10A0090	4	0.28	220	3	1.54
10A0100	6	0.55	220	3 1/2	3.52
10A0130	8	0.96	220	3 3/4	6.38
10A0150	10	1.43	220	4	9.9
10A0180	12	2.03	220	4 1/2	14.3
10A0200	14	2.79	220	5	19.58
10A0220	16	3.5	220	5 1/2	25.52
10A0225	20	5.37	220	3	39.82
10A0240	24	7.6	220	3	57.2